



● MAIN FEATURES

- **Multi-Digital** operation in P25 (Phases 1 & 2) and NXDN™ protocols
- **Mixed Digital & FM Analog Operation** allows intelligent migration in mixed sites and easy migration with digital radios in other sites
- **Large, Color 2.55" (154 x 422 pixels) TFT Display** for at-a-glance operational status checking
- **Easy to follow GUI** and **Multi-line Text** to convey more information
- **Dual Remote Control Head** Option and **Multi-Band (Multi RF Deck)** Control Option providing scalable configurations for various operations and applications
- **Built-In GPS Receiver** for effective fleet management
- **Bluetooth® Module built-in** for hands-free operation
- Renowned KENWOOD Audio Quality can be achieved with **Active Noise Cancelling** that utilizes built-in DSP with two microphones for suppression of ambient noise
- Built-in **56-bit DES Encryption**
- Optional **256-bit AES Encryption**
- **microSD/microSDHC Memory Card Slot** for increased memory capacity for "Voice & Data"
- **IP54/55** and **MIL-STD-810 C/D/E/F/G**

● GENERAL FEATURES

- 5 W to 50 W (136-174 MHz) Models
- 5 W to 45 W (380-470, 450-520 MHz) Models
- Maximum of 4,000 CH/Radio capacity, 512 CH/Zone, 128 Zones
- DB-25 Accessory Connector
- 4 W Speaker Audio

● DIGITAL – P25 MODE

- P25 Phase 1 Conventional/Trunked Operation
- P25 Phase 2 Trunked Operation
- AMBE+2™ Enhanced Vocoder
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit
- Encryption Key Zeroize & Retention
- P25 GPS Location
- P25 Over-the-Air Re-keying
- P25 Over-the-Air Programming*2

● DIGITAL – NXDN™ MODE

- NXDN™ Conventional Operation
- NXDN™ Type-C Trunked Operation
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channel Spacing
- Over-the-Air Alias
- Over-the-Air Programming*1
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging*2
- Remote Stun/Kill*2
- Remote Check*2
- Short & Long Data Messages*2
- GPS Location
- NXDN™ Digital Scrambler Included

*1 Requires KENWOOD OTAP Management software.

*2 Requires NX subscriber unit PC serial interface compatible software application (e.g. KENWOOD AVL & Dispatch Messaging software) or hardware (e.g. console).

● FM MODES – GENERAL

- Conventional & LTR Zones
- FleetSync®/II: PTT ID ANI / Caller ID Display, Selective / Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT & Two-Tone
- Built-in Voice Inversion Scrambler

MULTIPLE CONFIGURATIONS (OPTION)

The NX-5700(B)/5800(B) allows users to create a variety of configurations to suit different requirements by combining different options.

- **Single Remote Control Head x Single RF Deck:**
The simplest configuration can be achieved by turning the front control panel of the NX-5700/5800 into a Remote Control Head.
- **Single Remote Control Head x Multi RF Decks*:**
You can operate two radios (e.g. VHF and UHF bands) as if they were one by adding an NX-5700B/5800B RF Deck.
- **Dual Remote Control Heads x Single RF Deck*:**
One controller can be mounted on the dashboard, with the other at the rear.
- **Dual Remote Control Heads x Multi RF Decks*:**
This adds the convenience of a dual control head to the above configuration. Advantage: 2 operators can control 2 radios (e.g. VHF and UHF bands) from separate control heads.

*Available later



OPTIONAL ACCESSORIES

■ NX-5700B/5800B

RF DECK

■ KCH-19

BASIC CONTROL HEAD KIT



■ KCH-20R*

FEATURED CONTROL HEAD

■ KRK-15B

CONTROL HEAD REMOTE KIT (Adapter for the RF Deck)



■ KRK-14H

CONTROL HEAD INTERFACE KIT (Adapter for the Head)



■ KCT-71

REMOTE CONTROL CABLE (Available in 3 lengths of 17 ft (5.2 m), 25 ft (7.6 m), 1.6 ft (0.5 m)*)



■ KWD-AE30/AE31

SECURE CRYPTOGRAPHIC MODULE

■ KPG-180AP*

OTAP MANAGER

*Available later

Existing accessories compatible with the NX-5700/5800

■ KMC-35

MICROPHONE



■ KMC-36

KEYPAD MICROPHONE



■ KES-3

EXTERNAL SPEAKER (Compact low profile; φ3.5 mm plug)



■ KES-5

EXTERNAL SPEAKER (40 W max input, Requires KAP-2)



■ KCT-23

DC POWER CABLE M: 10 ft (3 m) / M3: 23 ft (7 m)




■ KCT-46

IGNITION SENSE CABLE



■ KLF-2

LINE FILTER



■ KMB-10

KEY LOCK ADAPTER



■ KAP-2

HORN ALERT/P.A. RELAY UNIT




■ KRA-40G

GPS ACTIVE ANTENNA



■ KPS-15

DC POWER SUPPLY (23 A max)



SPECIFICATIONS

GENERAL	Mobile Radios		
	NX-5700(B)	NX-5800(B)	
Frequency Range	136-174 MHz	Type 1: 450-520 MHz Type 2: 380-470 MHz	
Max. Channels Per Radio	1024 (Up to 4000 channels with option)		
Number of Zones	128		
Max. Channels Per Zone	512		
Channel Spacing	Analog	12.5/15/20/25*/30* kHz	
	Digital	12.5/25* kHz	
Power Supply	13.6 V DC ±15 %		
	Standby	0.45 A	
Current Drain	RX	2.3 A	
	TX	13 A	
Operating Temperature	-22° F to +140 °F (-30 °C to +60 °C)		
Frequency Stability	±1.0 ppm		
Dimensions (W x H x D)	6.69 x 1.89 x 6.93 in. (170 x 48 x 176 mm)		
Radio with Control Head, Projections Not Included	6.69 x 1.89 x 6.93 in. (170 x 48 x 176 mm)		
Weight: Radio with Control Head	3.53 lbs (1.6 kg)		

*25 and 30 kHz are not included in the models sold in the USA or US territories.

Analog measurements made per TIA 603 and specifications shown are typical. Digital measurements made per TIA 102CAAA and specifications shown are typical.

Details and timing of firmware and software updates are subject to change without notice. Specifications are subject to change without notice, due to advancements in technology.

RECEIVER	Mobile Radios	
	NX-5700(B)	NX-5800(B)
Sensitivity	NXDN 6.25 kHz Digital (3 % BER)	0.20 µV
	NXDN 12.5 kHz Digital (3 % BER)	0.25 µV
	P25 Digital (5 % BER)	0.25 µV
	P25 Digital (1 % BER)	0.40 µV
Selectivity	Analog (12dB SINAD)	0.25 µV
	P25 Digital	63 dB
	Analog @ 12.5 kHz	71 dB
Intermodulation	Analog @ 25 kHz	81 dB
Spurious Rejection	87 dB	85 dB
Audio Distortion	2 %	
Audio Output Power	4 W/4 Ω (Remote Control Head: 3 W/4 Ω)	
TRANSMITTER	NX-5700(B)	NX-5800(B)
RF Power Output Power	50 to 5 W	45 to 5 W
Spurious Emission	-73 dB	-75 dB
FM Hum & Noise	Analog @ 12.5 kHz	45 dB
	Analog @ 25 kHz	50 dB
Audio Distortion	2 %	
Emission Designator	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

APPLICABLE MIL-STD & IP

MIL Standard	810C Methods/ Procedures	810D Methods/ Procedures	810E Methods/ Procedures	810F Methods/ Procedures	810G Methods/ Procedures
Low Pressure	500.3/I	500.2/I, II	500.3/I, II	500.4/I, II	500.5/I, II
High Temperature	501.3/I, II	501.2/I, II	501.3/I, II	501.4/I, II	501.5/I, II
Low Temperature	502.1/I	502.2/I, II	502.3/I, II	502.4/I, II	502.5/I, II
Temp. Shock	503.1/I	503.2/I	503.3/I	503.4/I, II	503.5/I
Solar Radiation	505.3/I	505.2/I	505.3/I	505.4/I	505.5/I
Rain*1	506.1/I, II	506.2/I, II	506.3/I, II	506.4/I, III	506.5/I, III
Humidity	507.1/I, II	507.2/II, III	507.3/II, III	507.4	507.5/II
Salt Fog	509.3/I	509.2/I	509.3/I	509.4	509.5
Dust	510.1/I	510.2/I	510.3/I	510.4/I, III	510.5/I
Vibration	514.2/VIII, X	514.3/I	514.4/I	514.5/I	514.6/I
Shock	516.2/I, II, V	516.3/I, IV, V	516.4/I, IV, V	516.5/I, IV, V	516.6/I, IV, V
International Protection Standard					
Dust & Water	IP54, IP55*2				

*1: Blowing rain protection for the mobile radio's Remote Control Head only. *2: IP54: RF Deck of the mobile radio; IP55: Remote Control Head for the mobile radio

● The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. ● SD and microSD are trademarks of SD-3C, LLC in the United States, and/or other countries ● AMBE+2™ is a trademark of Digital Voice Systems Inc. ● Windows® is a registered trademark of Microsoft Corporation. ● NXDN™ is a trademark of JVCENWOOD Corporation and Icom Inc. ● NEXEDGE® is a registered trademark of JVCENWOOD Corporation.

JVCENWOOD USA Corporation

Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.

Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

www.kenwood.ca



CL-805K-E-2