

## A-3575 75-Watt Multiband Amplifier



### Overview

The A-3575 provide the same trademark power and performance associated with all Ultralife amplifiers. Users benefit from consistent amplification across the 30-512 MHz range. Operators select 12, 25 and 50/75 watts. The 50/75 watt power setting provides 75 watts of power in the UHF TACSAT uplink band and 50 watts everywhere else.

Each unit comes with an easy to install 'shock and vibration' isolating mounting tray and fused power cable. The amp weighs less than 11.5 pounds with the included shock tray, and is sealed, watertight, and weather-resistant.

The amp supports Demand Assigned Multiple Access (DAMA) and other JTRS waveforms. The A-3575 is combat-proven, and MIL-STD 461E and MIL-STD 810F compliant.

### Features

- ▶ **JITC compliant**
- ▶ **Supports DAMA & other JTRS waveforms**
- ▶ **75 watts for UHF SATCOM**
- ▶ **Multilevel power control for 12, 25 and 50/75 watts**
- ▶ **Weighs less than 11.5 lbs. with shock tray**
- ▶ **Radio manufacturer independent**



Follow Us Online:



[www.ultralifecorporation.com/commsys](http://www.ultralifecorporation.com/commsys)  
800-332-5000 | [orders@ulbi.com](mailto:orders@ulbi.com)

## A-3575 Technical Specifications

<b>Part No.</b>	A-3575
<b>Size (H x W x D - inches) (With shock tray assembly)</b>	10.12 x 6.75 x 2.8
<b>Weight</b>	< 12 lbs. including shock tray
<b>Remote Control</b>	RS-232
<b>Frequency Range</b>	30-512 MHz
<b>DC Power</b>	10-36 VDC
<b>DC Input Power - Transmit</b>	420 watts (max)
<b>DC Input Power - Receive</b>	20 watts
<b>RF Input</b>	3-8 watts (5 watts nominal)
<b>RF Output (AM)</b>	12, 25, & 50 watts PEP 110-512 MHz
<b>RF Output (FM)</b>	12 & 25 watts: 30-512 MHz 50 watts: 30-219 & 325-512 MHz 75 watts: 220-324 MHz
<b>RX Path Insertion Loss</b>	< 1.5 dB
<b>RX Path VSWR</b>	< 2:1
<b>Bypass Path Insertion Loss</b>	< 1.5:1 dB
<b>AM Distortion</b>	< 15% 110-512 MHz
<b>MTBF</b>	15,000 hours
<b>Duty Cycle</b>	33% @ 60° C = 50 watts
<b>Operating Temperature</b>	-40° to +60° C
<b>Weather Resistant</b>	IP-65
<b>Finish</b>	Black, anodized
<b>MIL-STD-461E</b>	Certified
<b>MIL-STD-810F</b>	Certified



[www.ultralifecorporation.com/commsys](http://www.ultralifecorporation.com/commsys)  
800-332-5000 | [orders@ulbi.com](mailto:orders@ulbi.com)

Follow Us Online:

