



ZONITH BT RECEIVER, MODEL BTR-01

DATASHEET

ENCLOSURE

Size: L:120 x W:120 x H:25 mm
IP Type: IP54
Weight: 172 g
Color: White

BLUETOOTH TECHNICAL DATA

Protocols: Bluetooth **v4.2 BR/EDR** and Bluetooth Low Energy (**BLE**)

APPROVALS

FCC, CE, IC

TRANSMITTER

Radio: Class-1, Class-2, Class-3 Transmitter
Frequency: 2.4 – 2.485 GHz
Adaptive Frequency Hopping (AFH)
Transmit Power: Min: -12dBm, Max +12dBm,
Typical: 0dBm (1mW)
Sensitivity @30.8% PER: Typ. -97dBm

NETWORK INTERFACE

Standard IEEE 802.3af
Physical Layer: 10/100 Base-T
Data Rate: 10/100 Mbps
Connector: RJ-45

POWER INTERFACE

The unit can be powered over either Ethernet or via external power supply.

IEEE 802.3af

Power over Ethernet
(PoE) Supports
Endspan and Midspan

External Power Supply:

Screw terminal connector
Operating voltage:
6 - 12 VDC, 1.A.

Power Consumption: <2W (No
Expansion). Typical 1W.

AMBIENT TEMPERATURES

Operating: Max: 55 °C, Min: -10 °C
Storage: Max: 80 °C, Min: -20 °C



Screw terminal connector



Disclaimer:

Zonith A/S makes no warranties that all functionality is supported neither by the local network nor by the selected Bluetooth devices used by the system. Specifications are subject to change without notice. All product or service names are the property of their respective owners.